DEMKO Certificate

Certificate
D-11774

Issue date
2026-07-24

Expiration date
2031-06-02

This is to acknowledge that

SCHNEIDER ELECTRIC INDUSTRIES SAS

1884 Boulevard de la Defense Nanterre 92000
France
has had

Junction box for use in trunking system

20002339, **20002340**, **20002341**

evaluated and meets the requirements of the standard

EN IEC 60670-1:2021, EN IEC 60670-1:2021/A11:2021

Test Report Nos.
SE-S-2600483 issued on 2026-06-02

Certification Manager
Thomas Wilson

UL International Demko A/S, Borupvang 5A, 2750 Ballerup, Denmark, Tel. +45 44 85 65 65

This is to certify that representative sample(s) of the Product described herein ("Product") have been investigated and found in compliance with the Standard(s) indicated on this Certificate, in accordance with the D-Mark Requirements. As specified in the respective sections below the Designated Certificate holder is entitled to use the D-Mark or its alternative for cables, for the Certified Product manufactured at the production site(s) identified above, in accordance with the D-Mark Service Agreement, including without limitation the D-Mark Testing and Certification Services Service Terms. Only those Products bearing the D-Mark should be considered as being covered by UL Solutions' D-Mark Service. This Certificate shall remain valid through the expiration date, unless terminated earlier in accordance with the Service Agreement including without limitation if the Standard identified on this Certificate is amended or withdrawn prior the expiration date.

DEMKO CERTIFICATE
TECHNICAL DETAILS

Production site(s)

Schneider Electric Elda S.A.
ul. Bugno 1 Szczecinek 78 400
Poland

Trademark

THORSMAN

Ratings

500V

Additional Information

Technical Data:
Product information Flush mounted boxes of insulating material in white colour. The boxes are provided with anchorage for flexible/sheathed cable diam. 8,2-14 mm. See table below.

Packaging type	Model	Description
MIB-A1	20002339	Limited for built-in use in cable trunking system for single flush mounted accessories. Dimension inner ca 68x65 mm, depth 40 mm, for accessories with fixing distance of 60 mm. For single accessories and alternative provided with 2 insulating frame no. 20038167 (MIB-A1D3).
MIB-A2	20002340	Limited for built-in use in cable trunking system for double flush mounted accessories. Dimension inner ca 135x67 mm, depth 40 mm, for accessories with fixing distance of 60 mm.
MIB-J	20002341	Junction box, limited for built-in use in cable trunking system. Dimension inner ca 67x67 mm, depth 36 mm for floating terminals.

Certificate No. D-11774
Date of Issue 2026-07-24

Certification Mark D-Mark

The D-Mark, as displayed below, shall appear on certified products only. Except as specified below the Mark shall be legible and no Minimum size is specified.



The size of the Mark may be reduced or enlarged on the condition that it remains readable and that the proportions of width and height are kept. The use of dark text for the D-Mark on light backgrounds and light text on dark backgrounds is permitted.

The D-Mark may appear on a label, nameplate, or may be cast, stamped or molded into the product. When appearing on a label or nameplate, the Manufacturer's name or trademark along with a model number are also required on that same label or nameplate. If cast, stamped or molded, the Certificate Manufacturer's name or trademark and model number shall also appear elsewhere on the product

When putting the product on the EU market, the manufacturer's name, trademark or mark of origin must be affixed in a clearly visible location and position on the product, on the package and in the user manual. It can be affixed by label, be directly imprinted, or cast or molded into the product.

Where the size of the product does not allow the Mark, the manufacturer's name, trademark, mark of origin and model number to be legible, and appearance on a label is not desired, it is allowed to cast, stamp or mold the Mark into the product, in a size which is not visible to the naked eye, provided the legible Mark, the manufacturer's name, trademark or mark of origin and model number appears on the package and in the user manual.

Alternate certification Mark for cables

As an alternative to the D-Mark specified above the alternate D-Mark, displayed below, can appear on certified cables only. Minimum size is not specified, as long as the mark is legible.

⊲DEMKO⊳

The alternate D-Mark may be cast, stamped or molded into the cable and continue throughout the length of the cable as specified in the applicable cable standard.

All content shall be in accordance with the details provided on this D-Mark Certificate.